

## DUOGRASS<sup>M</sup>

11

13

15

### MATERIAL SPECIFICATIONS

#### Yarn

TTC THIOLON TS XT 100% PE Fibrillated  
 UV Resistant  
 Straight  
 10.000/2 D-Tex (+/- 5%)  
 110 Micron thickness  
 5mm width

#### Color

Dark Green - Lime Green

#### Primary Backing

Ten Cate H16 backing with fleece

#### Secondary Backing

Carboxylated (SBR) latex with 4mm perforation holes



### TECHNICAL SPECIFICATIONS

	11mm	13mm	15mm
<b>Pile Height</b>	11 mm	13 mm	15 mm
<b>Total Pile Height</b>	28mm	32mm	36 mm
<b>Gauge</b>	5/16"	5/16"	5/16"
<b>Stiches</b>	220 S/M	220 S/M	220 S/M
<b>Stiches per m<sup>2</sup></b>	27720 /m <sup>2</sup>	27720 /m <sup>2</sup>	27720 /m <sup>2</sup>
<b>Pile Weight</b>	820 gr/m <sup>2</sup>	940 gr/m <sup>2</sup>	1060 gr/m <sup>2</sup>
<b>Total Weight</b>	1940 gr/m <sup>2</sup>	2050 gr/m <sup>2</sup>	2170 gr/m <sup>2</sup>
<b>Coating</b>	Latex 1000gr/m <sup>2</sup>	Latex 1000gr/m <sup>2</sup>	Latex 1000 gr/m <sup>2</sup>
<b>Permeability</b>	60 lt/min	60 lt/min	60 lt/min

### INFILL MATERIALS

<b>Sand</b>	25 kg – 30 kg/m <sup>2</sup>
<b>Sand Type</b>	Siliceous, round, washed and dried
<b>Sand Size</b>	0,2 – 0,63 mm
<b>Rubber</b>	6 – 9 kg/m <sup>2</sup>
<b>Rubber Type</b>	SBR
<b>Rubber Size</b>	0,8 – 2,5 mm
<b>Shock Pad</b>	25mm (in situ)

### LINES

<b>Color</b>	White- Yellow- Red Clay
<b>Width</b>	8 - 10 cm

### MAINTENANCE AND WARRANTY

Ask for the maintenance documentation available on request. All multisport series under 5 years have **ilkesport** warranty under right maintenance conditions.

All measurements are +/- within 10%. ilkesport, in accordance with its policy of development, reserve the right to alter above specifications.