

PREMIUM^H

11

13

15

MATERIAL SPECIFICATIONS

Yarn

100% THIOLON PE Fibrillated (KDK)
 UV Resistant
 Straight
 7.300 D-Tex (+/- 5%)
 60 Micron thickness
 11mm width

Color

Verde

Primary Backing

Ten Cate D12 backing with Angel Hair

Secondary Backing

Carboxylated (SBR) latex with 4mm perforation holes



TECHNICAL SPECIFICATIONS

	11mm	13mm	15mm	20mm
Pile Height	11 mm	13 mm	15 mm	20 mm
Total Pile Height	28 mm	32 mm	36 mm	46 mm
Gauge	3/16"	3/16"	3/16"	3/16"
Stiches	200 S/M	200 S/M	200 S/M	200 S/M
Stiches per m²	42000 /m ²	42000 /m ²	42000 /m ²	42000 /m ²
Pile Weight	910 gr/m ²	1040 gr/m ²	1170 gr/m ²	1490 gr/m ²
Total Weight	2130 gr/m ²	2250 gr/m ²	2370 gr/m ²	2680 gr/m ²
Coating	Latex 1000gr/m ²	Latex 1000gr/m ²	Latex 1000 gr/m ²	Latex 1000 gr/m ²
Permeability	60 lt/min	60 lt/min	60 lt/min	60 lt/min

INFILL MATERIALS

Sand	25 kg – 30 kg/m ²
Sand Type	Siliceous, round, washed and dried
Sand Size	0,2 – 0,63 mm
Rubber	6 – 9 kg/m ²
Rubber Type	SBR
Rubber Size	0,8 – 2,5 mm
Shock Pad	25mm (in situ)

LINES

Color	White- Yellow- Red Clay
Width	8 - 10 cm

MAINTENANCE AND WARRANTY

Ask for the maintenance documentation available on request. All PremiumH series under 5 years have **ilkesport** warranty under right maintenance conditions.

All measurements are +/- within 10%. ilkesport, in accordance with its policy of development, reserve the right to alter above specifications.