

PREMIUM^M

11

13

15

MATERIAL SPECIFICATIONS
Yarn

100% THIOLON PE Fibrillated
 UV Resistant
 Straight
 8.800 D-Tex (+/- 5%)
 100 Micron thickness
 9mm width

Color

Verde

Primary Backing

Ten Cate H16 backing with Angel Hair

Secondary Backing

Carboxylated (SBR) latex with 4mm perforation holes


TECHNICAL SPECIFICATIONS

	11mm	13mm	15mm
Pile Height	11 mm	13 mm	15 mm
Total Pile Height	28mm	32mm	36 mm
Gauge	3/16"	3/16"	3/16"
Stiches	200 S/M	200 S/M	200 S/M
Stiches per m²	42000 /m ²	42000 /m ²	42000 /m ²
Pile Weight	1100 gr/m ²	1250 gr/m ²	1410 gr/m ²
Total Weight	2360 gr/m ²	2510 gr/m ²	2670 gr/m ²
Coating	Latex 1000gr/m ²	Latex 1000gr/m ²	Latex 1000 gr/m ²
Permeability	60 lt/min	60 lt/min	60 lt/min

INFILL MATERIALS

Sand	25 kg – 30 kg/m ²
Sand Type	Siliceous, round, washed and dried
Sand Size	0,2 – 0,63 mm
Rubber	6 – 9 kg/m ²
Rubber Type	SBR
Rubber Size	0,8 – 2,5 mm
Shock Pad	25mm (in situ)

LINES

Color	White- Yellow- Red Clay
Width	8 - 10 cm

MAINTENANCE AND WARRANTY

Ask for the maintenance documentation available on request. All multisport series under 5 years have **ilkesport** warranty under right maintance conditions.

All measurements are +/- within 10%. ilkesport, in accordance with its policy of development, reserve the right to alter above specifications.