

## SLICE

20

23

25

### MATERIAL SPECIFICATIONS

**Yarn**

100% THIOLON PE Fibrillated  
 UV Resistant  
 Straight  
 8.800 D-Tex (+/- 5%)  
 100 Micron thickness  
 9mm width

**Color**

Verde

**Primary Backing**

TenCate® H16 backing with Angel Hair

**Secondary Backing**

Carboxylated (SBR) latex with 4mm perforation holes



### TECHNICAL SPECIFICATIONS

	20mm	23mm	25mm
<b>Pile Height</b>	20 mm	23 mm	25 mm
<b>Total Pile Height</b>	46mm	52mm	56 mm
<b>Gauge</b>	3/8"	3/8"	3/8"
<b>Stiches</b>	150 S/M	150 S/M	150 S/M
<b>Stiches per m<sup>2</sup></b>	15750 /m <sup>2</sup>	15750 /m <sup>2</sup>	15750 /m <sup>2</sup>
<b>Pile Weight</b>	675 gr/m <sup>2</sup>	775 gr/m <sup>2</sup>	850 gr/m <sup>2</sup>
<b>Total Weight</b>	1850 gr/m <sup>2</sup>	1950 gr/m <sup>2</sup>	2000 gr/m <sup>2</sup>
<b>Coating</b>	Latex 1000gr/m <sup>2</sup>	Latex 1000gr/m <sup>2</sup>	Latex 1000 gr/m <sup>2</sup>
<b>Permeability</b>	60 lt/min	60 lt/min	60 lt/min

### INFILL MATERIALS

<b>Sand</b>	20 – 25 kg/m <sup>2</sup>
<b>Sand Type</b>	Siliceous, round, washed and dried
<b>Sand Size</b>	0,2 – 0,63 mm
<b>Rubber</b>	
<b>Rubber Type</b>	
<b>Rubber Size</b>	
<b>Shock Pad</b>	

### LINES

<b>Color</b>	White- Yellow- Red Clay
<b>Width</b>	8 - 10 cm

### MAINTENANCE AND WARRANTY

Ask for the maintenance documentation available on request. All tennis series under 7 years have **ilkesport** warranty under right maintenance conditions.

All measurements are +/- within 10%. ilkesport, in accordance with its policy of development, reserve the right to alter above specifications.