

STRIKE_{NON-INFILL}

25

30

35

MATERIAL SPECIFICATIONS

Yarn

TTC THOLON KDK 12000 100% PE Fibrillated
 UV Resistant, Straight, 7.300 D-Tex (+/- 5%)
 210 Micron thickness
 ALS C Shape Yarn 100% PE Monofilament
 195 Micron thickness
 Non Fibrillated Spine Shape Yarn 1,6mm width

Color

Field Green-Dark Green-Lime Green

Primary Backing

TenCate® D12 backing with fleece

Secondary Backing

Carboxylated (SBR) latex with 4mm perforation holes



TECHNICAL SPECIFICATIONS

	25mm	30mm	35mm
Pile Height	25 mm	30 mm	35 mm
Total Pile Height	56mm	66mm	76 mm
Gauge	5/16"	5/16"	5/16"
Stiches	180 S/M	180 S/M	180 S/M
Stiches per m²	22680 /m ²	22680 /m ²	22680 /m ²
Pile Weight	980 gr/m ²	1160 gr/m ²	1330 gr/m ²
Total Weight	2100 gr/m ²	2260 gr/m ²	2430 gr/m ²
Coating	Latex 1000gr/m ²	Latex 1000gr/m ²	Latex 1000 gr/m ²
Permeability	60 lt/min	60 lt/min	60 lt/min

INFILL MATERIALS

Sand	5 kg/m ²
Sand Type	Siliceous, round, washed and dried
Sand Size	0,2 – 0,63 mm
Rubber	no
Shock Pad	25mm (in situ)

MAINTENANCE AND WARRANTY

Ask for the maintenance documentation available on request. All soccer series under 8 years have **ilkesport** warranty under right maintance conditions.

All measurements are +/- within 10%. ilkesport, in accordance with its policy of development, reserve the right to alter above specifications.

LINES

Color	White- Yellow- Red Clay
Width	8 - 10 cm