

## BINDER

### PU Binder for Finisher Application

A solvent free, one component polyurethane based adhesive, binder. Reaction products of MDI with hidroxyolated compounds.

#### Application fields:

The binder is suitable for the industrial rubber floorings and sports floor.

#### Features

- Solvent free
- High adhering power
- Resistant to moisture and weathering
- Transport at 20°C



<b>Density</b>	1,10 gr/cm <sup>3</sup>
<b>Viscosity</b>	4.500 mPas ( at +25°C)
<b>Chemical Resistance</b>	After 7 days
<b>Storage and Transport T.</b>	-20°C/+50°C
<b>Waiting Time</b>	None
<b>Color</b>	Light yellow

#### Application:

Rubber, SBR rubber and EPDM rubber granules mixed in a suitable mixer as a 5/1 (17%-20%) ratio with the Binder. After this application the mixture spilled into the finisher machine. Finally material can be applied on to the surface with required thickness.

#### Storage:

6 months under normal climatic conditions.

#### Health & Safety:

If it touches with skin wash with water and soap. Do not use the empty packages for the storage of nutriment.



\* The information and recommendations contained herein are based on the current state of our knowledge. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained here.

\*\*Please check the website or contact us to get more information.