

ACRYLIC SYSTEM

MATERIAL SPECIFICATIONS

Made

Acrylic / +Cushion Rubber

Color

All colors

Resistance

All climatic conditions
Not flammable

Suitable for

Indoor/Outdoor sport areas
Fitness centers and gymnasiums
Tennis courts
Multipurpose sport fields



ACRYLIC Standard System

It is composed of components that are produced with 100% pure acrylic latex polymers. It is the most economical system of the ACYRLIC series. It is a covering that can be used during all four seasons and that it has an aesthetical, long-lasting and textured structure with a topcoat covering colored with UV resistant pigments provide the players with an opportunity to play comfortably and with a good performance. As it is used as a tennis court floor covering, it is also safely used in multipurpose outdoor play fields for basketball, volleyball, and handball. It is classified as number 2 by ITF (ITF pace rate :2). As it is recommended to be used on the asphalt floor, it can also be used on suitable concrete floors after the surface preparations are made with proper primer systems.

Components:

ACRYLIC PRIMER 367-28

Acrylic Primer 367-28 is % 100 acrylic latex based emulsion to improve bond of acrylic court system to concrete. It is ready to use product , no need to dilute.

ACRYLIC RESURFACER 367-30

ACRYLIC RESURFACER 367-30 is % 100 acrylic latex based resurfacer which is blended with sand and water.

Principal Characteristics:

- It is used as a resurfacer before application of PRECOAT 367-200 (Acrylic Color Topcoat)
- Fills voids and hides the profile of aggregates in concrete or asphalt floor.
- Makes the concrete or asphalt floors smoother and increase the yield of subsequent PRECOAT

PRECOAT 367-200

367-200 is a quartz filled % 100 acrylic latex based textured tennis topcoat.

OVERLINE 367-F

OVERLINE 367-F is % 100 acrylic latex based high hiding line paints.

GLOSSCOAT 367-T

Glosscoat 367-T is a ready to use, 100% acrylic latex polymer, clear drying emulsion formulated as a protective top coat for ACRYFLEX T Tennis Court Systems

*Please get in touch with us for the TDS and MSDS documents of the components.

ACRYLIC Cushion System

The system has acquired an elastic structure with RUBBER coat that was created by mixing the very special granulometric rubber powder in a %100 pure acrylic latex polymer. As our other systems, ACRYLIC Cushion which is used for multipurpose in outdoors provides a comfortable, safe and high performance game for the player thanks to its impact absorber floor feature. ACRYLIC Cushion which has to be applied on concrete infrastructure may also be applied on concrete floors whose surface preparation is properly made. It is classified as number 1 by ITF Its average application thickness is 3 mm. ITF Pace Rate :1)

Components:

ACRYLIC PRIMER 367-28

Acrylic Primer 367-28 is % 100 acrylic latex based emulsion to improve bond of acrylic court system to concrete. The product is ready to use. No need to dilute.

ACRYLIC RESURFACER 367-30

ACRYLIC RESURFACER 367-30 is % 100 acrylic latex based resurfacer which is blended with sand and water.

Principal Characteristics:

- It is used as a resurfacer before application of PRECOAT 367-200 (Acrylic Color Topcoat)
- Fills voids and hides the profile of aggregates in concrete or asphalt floor.
- Makes the concrete or asphalt floors smoother and increase the yield of subsequent PRECOAT

RUBBER (CUSHION) 367-40

RUBBER 367-40 is rubber filled % 100 acrylic latex based cushion coating.

PRECOAT 367-200

PRECOAT 367-200 is a quartz filled % 100 acrylic latex based textured tennis topcoat.

OVERLINE 367-F

OVERLINE 367-F is % 100 acrylic latex based high hiding line paints.

GLOSSCOAT 367-T

Glosscoat 367-T is a ready to use, 100% acrylic latex polymer, clear drying emulsion formulated as a protective top coat for ACRYLIC Tennis Court Systems



*Please get in touch with us for the TDS and MSDS documents of the components.

ACRYLIC Cushion Plus System

A professional system with its impact absorbing feature increased with 8 coats of RUBBER, ACRYLIC Cushion Plus provides a game at a medium speed. The system creates a long lasting floor that may be used during four seasons. The combination of 8 different colors enables you to create field floors of different colors. Not requiring any maintenance, ACRYLIC Cushion Plus gives the player the joy of a professional game with its long lasting quality and comfort. It is classified as number 3 by ITF. (ITF Pace Rate :3)

Components:

ACRYLIC PRIMER 367-28

Acrylic Primer 367-28 is % 100 acrylic latex based emulsion to improve bond of acrylic court system to concrete. The product is ready to use. No need to dilute.

ACRYLIC RESURFACER 367-30

ACRYLIC RESURFACER 367-30 is % 100 acrylic latex based resurfacer which is blended with sand and water.

Principal Characteristics:

- It is used as a resurfacer before application of PRECOAT 367-200 (Acrylic Color Topcoat)
- Fills voids and hides the profile of aggregates in concrete or asphalt floor.
- Makes the concrete or asphalt floors smoother and increase the yield of subsequent PRECOAT

RUBBER (CUSHION) 367-40

RUBBER 367-40 is rubber filled % 100 acrylic latex based cushion coating.

PRECOAT 367-200

PRECOAT 367-200 is a quartz filled % 100 acrylic latex based textured tennis topcoat.

OVERLINE 367-F

OVERLINE 367-F is % 100 acrylic latex based high hiding line paints.

GLOSSCOAT 367-T

Glosscoat 367-T is a ready to use, 100% acrylic latex polymer, clear drying emulsion formulated as a protective top coat for ACRYLIC Tennis Court Systems



*Please get in touch with us for the TDS and MSDS documents of the components.